

Specifications — CPM200, CPM208

General

Rack mount No, but furniture mountable
Enclosure type Metal
Enclosure dimensions

CAUTION Refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face; the unit’s MAAP and connector access side is underlined. Extron is not responsible for miscut mounting holes.

CPM200

Top plate (outer rim) 4.0" W x 4.0" D (10.2 cm W x 10.2 cm D)
Surface cutout (inside rim)
3.5" diameter (8.9 cm diameter)
Box (under surface) . 3.5" H x 2.5" W (front of unit) x 2.5" D (8.9 cm H x 6.4 cm W x 6.4 cm D)

CPM208

Top plate (outer rim) 6.75" W x 4.75" D (17.1 cm W x 12.1 cm D)
Surface cutout (inside rim)
5.88" W (front of unit) x 3.63" D (14.9 cm W x 9.22 cm D)
Box (under surface) . 3.5" H x 5.25" W (front of unit) x 3.4" D (8.9 cm H x 13.3 cm W x 8.6 cm D)

Product weight
CPM200 0.6 lbs (0.3 kg)
CPM208 1.1 lbs (0.5 kg)
Shipping weight 2 lbs (1 kg)
Vibration ISTA 1A in carton (International Safe Transit Association)
Listings UL, CUL
Compliances CE, FCC Class A, VCCI, AS/NZS, ICES
Warranty 3 years parts and labor

NOTE Specifications are subject to change without notice.

7.51-011906-D3-111512