

Specifications

FOX 3G HD-SDI

NOTE: The FOX 3G HD-SDI is a transceiver that can function as a transmitter and/or as a receiver. Two units are required for a transmitter-receiver system with one fiber optic cable linking the two units. The FOX 3G HD-SDI is available in singlemode or multimode versions.

NOTE: These transceivers are class 1 laser products. They meet the safety regulations of IEC-60825.

NOTE: The FOX 3G HD-SDI P SM transceivers offer immunity to "pathological" signals, including test patterns defined by SMPTE Recommended Practice (RP) 178 and SMPTE RP 198 for SD-SDI, HD-SDI, and 3G-SDI.

NOTE: FOX 3G HD-SDI P SM transceivers are immune to pathological signals only when P model units are used in the transmitter, receiver, or Fiber Matrix Switcher boards. If the signal is routed through a matrix switcher without P model I/O boards, a FOX DA8, or a FOX SW8, the system does not provide immunity.

Optical fiber interconnection between transmitter and receiver

Number/type..... 1 fiber optic

NOTE: Only one fiber is required to transmit video and embedded audio and unidirectional data.

Connectors..... 1 LC connector

Operating distance

Singlemode 30 km (18.75 miles) with singlemode (SM) cables with an SM unit

Multimode 500 m (1640') with 62.5 μ m OM1 multimode (MM) cables with an MM unit

1 km (3280') with 50 μ m OM2 multimode (MM) cables with an MM unit

2 km (6561') with 50 μ m OM3/OM4 2000 MHz bandwidth laser optimized multimode (MM) cables with an MM unit

NOTE: Operating distance is approximate. These are typical maximum distances that may vary depending on factors such as fiber type, fiber bandwidth, connector splicing, losses, modal or chromatic dispersion, environmental factors, and kinks.

Nominal peak wavelength 850 nm for MM units; 1310 nm for SM units

Transmission power

Singlemode -5 dBm, typical

Multimode -5 dBm, typical

Maximum receiver sensitivity

Singlemode -18 dBm, typical

Multimode -12 dBm, typical

Optical loss budget

Singlemode 13 dB, maximum

Multimode 7 dB, maximum

Video

Signal type..... HD-SDI, SDI, and 3G-SDI digital video signals

Gain..... Unity

Resolution..... 8 or 10 bits, automatic

Data rates 270 Mbps, 1.485 Gbps, 2.970 Gbps

Operation standards

All models..... SMPTE 259M-C, SMPTE 292M, SMPTE 424M, ITU-R BT.601, ITU-R BT.1120

FOX 3G HD-SDI P SMPTE 297-2006, SMPTE RP 178, SMPTE RP 198

Auto data rate lock..... Yes

Specifications • FOX 3G HD-SDI (Continued)

Video input — transmitter

Number/signal type.....	1 single link SDI, HD-SDI, or 3G-SDI digital component video
Connectors.....	1 female BNC
Data rates	19 Mbps to 2.97 Gbps
Nominal level.....	0.8 Vp-p
Minimum/maximum levels.....	0.5 V to 1 Vp-p with no offset
Impedance.....	75 ohms
Return loss	≥15 dB @ 5 MHz to 1.5 GHz
DC offset (max. allowable).....	5 V
Input coupling	AC
Input cable equalization.....	Automatic for up to -30 dB of cable loss
3G-SDI	60 m (200') using Extron RG6 cable 45 m (150') using Extron RG59 cable
HD-SDI.....	120 m (400') using Extron RG6 cable 90 m (300') using Extron RG59 cable
SDI.....	150 m (500') using Extron RG6 cable 120 m (400') using Extron RG59 cable

Video output — receiver

Number/signal type.....	2 single link SDI, HD-SDI, or 3G-SDI digital component video
Connectors.....	2 female BNC
Re-clocking.....	Automatic for 270 Mbps, 1.485 Gbps, 2.97 Gbps, or bypassed for unrecognized rates
Nominal level.....	0.8 Vp-p
Minimum/maximum levels.....	0.5 V to 1.0 Vp-p
Impedance.....	75 ohms
Return loss	>25 dB @ 100 MHz
DC offset	±5 mV with input at 0 offset

General

Power supply.....	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 0.5 A, 6 watts
Power input requirements	12 VDC, 0.3 A
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	
Rack mount.....	Yes, with optional rack shelf kit
Furniture mount.....	Yes with optional through-desk or under-desk mounting kit
Pole mount.....	Yes, with optional pole mounting kit
Enclosure type	Metal
Enclosure dimensions	1.0" H x 4.3" W x 3.0" D (quarter rack wide) (2.5 cm H x 10.9 cm W x 7.6 cm D) (Depth excludes connectors.)
Product weight	0.5 lb (0.3 kg) per each unit
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety.....	CE, c-UL, UL
EMI/EMC.....	CE, C-tick, FCC Class A, ICES, VCCI
Warranty	3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.