

Specifications

HSA 200C

Video input

Number/signal type	1 VGA-QXGA RGBHV, RGBS, RGsB, RsGsBs, HDTV component video
Connectors	1 female 15-pin HD

Video output

Number/signal type	1 pass-through VGA-QXGA RGBHV, RGBS, RGsB, RsGsBs, HDTV component video
Connectors	5 female BNC on pigtailed

Audio input

Number/signal type	1 stereo, unbalanced
Connectors	1 female 3.5 mm stereo jack

Audio output

Number/signal type	1 pass-through stereo, unbalanced
Connectors	(1) 3.5 mm, direct insertion captive screw connector, 3 pole

General

Mounting	
Furniture mount	Yes
Min./max. table thickness	0.375" to 3.00" (0.95 cm to 7.62 cm)
Enclosure type	Metal
Enclosure dimensions	

CAUTION: Use the appropriate metal Extron routing template or refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face; the connector access side of the unit is underlined. Extron is not responsible for miscut mounting holes.

HSA 200C — USA models

Top plate (outer rim).....	6.50" diameter (16.51 cm diameter) circle
Top plate (inside tilt plate) ..	<u>4.34</u> " W x 3.00" D (<u>11.03</u> cm W x 7.62 cm D)
Surface cutout (inside rim)..	6.03 +0.00/-0.02" diameter (15.32 +0.00/-0.05 cm diameter) circle
Box (under surface).....	5.5" H x <u>5.2</u> " W (front of unit) x 4.3" D (14.0 cm H x <u>13.2</u> cm W x 10.9 cm D) without clamps 5.5" H x <u>8.4</u> " W (front of unit) x 4.3" D (14.0 cm H x <u>21.3</u> cm W x 10.9 cm D) with clamps

HSA 200C — international circular models

Top plate (outer rim).....	8.5" diameter (21.6 cm diameter) circle
Top plate (inside tilt plate) ..	<u>5.9</u> " W x 4.1" D (<u>15.1</u> cm W x 10.4 cm D)
Surface cutout (inside rim)..	8.03 +0.00/-0.02" diameter (20.40 +0.00/-0.05 cm diameter) circle
Box (under surface).....	4.0" H x <u>6.3</u> " W (front of unit) x 5.0" D (10.2 cm H x <u>15.9</u> cm W x 12.7 cm D) without clamps 4.0" H x <u>10.0</u> " W (front of unit) x 5.0" D (10.2 cm H x <u>25.3</u> cm W x 12.7 cm D) with clamps
Product weight.....	4.0 lbs (1.8 kg)
Shipping weight.....	7 lbs (4 kg)

Vibration ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance
Safety CE, c-UL, CSA C/US, UL
Warranty 3 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$.

NOTE: Specifications are subject to change without notice.

8 0-110810-D15-111512