

# Specifications

## HSA 200S

### Video input

Number/signal type .....	1 VGA-QXGA RGBHV, RGBS, RGsB, RsGsBs, HDTV component video
Connectors .....	1 female 15-pin HD

### Video output

Number/signal type .....	1 pass-through VGA-QXGA RGBHV, RGBS, RGsB, RsGsBs, HDTV component video
Connectors .....	5 female BNC on pigtailed

### Audio input

Number/signal type .....	1 stereo, unbalanced
Connectors .....	1 female 3.5 mm stereo jack

### Audio output

Number/signal type .....	1 pass-through stereo, unbalanced
Connectors .....	(1) 3.5 mm, direct insertion captive screw connector, 3 pole

### General

Mounting	
Furniture mount .....	Yes
Min./max. table thickness .....	0.375" to 3.00" (0.95 cm to 7.62 cm)
Enclosure type .....	Metal
Enclosure dimensions	

**CAUTION:** Use the appropriate metal Extron routing template or refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face; the connector access side of the unit is underlined. Extron is not responsible for miscut mounting holes.

#### HSA 200S — USA models

Top plate (outer rim).....	<u>6.47</u> " W x 5.125" D ( <u>16.43</u> cm W x 13.02 cm D)
Top plate (inside tilt plate) ..	<u>4.34</u> " W x 3.00" D ( <u>11.03</u> cm W x 7.62 cm D)
Surface cutout (inside rim)..	<u>6.00 +0.00/-0.02</u> " W x 4.65 +0.00/-0.02" D ( <u>15.24 +0.00/-0.05</u> cm W x 11.81 +0.00/-0.05 cm D)
Box (under surface) .....	5.5" H x <u>5.2</u> " W (front of unit) x 4.3" D (14.0 cm H x <u>13.2</u> cm W x 10.9 cm D) without clamps 5.5" H x <u>8.4</u> " W (front of unit) x 4.3" D (14.0 cm H x <u>21.3</u> cm W x 10.9 cm D) with clamps

#### HSA 200S — international square models

Top plate (outer rim).....	<u>8.18</u> " W x 6.375" D ( <u>20.79</u> cm W x 16.19 cm D)
Top plate (inside tilt plate) ..	<u>5.90</u> " W x 4.10" D ( <u>14.99</u> cm W x 10.41 cm D)
Surface cutout (inside rim)..	<u>7.70 +0.00/-0.02</u> " W x 5.90 +0.00/-0.02" D ( <u>19.56</u> +0.00/-0.05 +cm W x 14.99 0.00/-0.05 +cm D)
Box (under surface) .....	4.0" H x <u>6.3</u> " W (front of unit) x 5.0" D (10.2 cm H x <u>15.9</u> cm W x 12.7 cm D) without clamps 4.0" H x <u>10.0</u> " W (front of unit) x 5.0" D (10.2 cm H x <u>25.3</u> cm W x 12.7 cm D) with clamps

Product weight.....	4.0 lbs (1.8 kg)
Shipping weight.....	7 lbs (4 kg)
Vibration .....	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety .....	CE, c-UL, CSA C/US, UL
Warranty .....	3 years parts and labor

**NOTE:** All nominal levels are at  $\pm 10\%$ .

**NOTE:** Specifications are subject to change without notice.

8 0-110810-D15-111512