

Specifications — IPA T IPA

General

Connectors	1 RJ-45 female connector for pass-through input 1 RJ-45 female connector for power and pass-through output
Data rate	10/100Base-T, half/full duplex with autodetect
Power input	Supplied by an attached external power supply: 100 VAC to 240 VAC, 50/60 Hz, external, autoswitchable; to 48 VDC, 0.3 A, regulated
Power output	48 VDC, IEEE 802.3af
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount	Yes, with optional 1U 9.5" deep rack shelf kit, part #60-190-01; or the 1U 3.5" deep VersaTools® rack shelf kit, part #60-190-20 Also under-furniture mountable with optional bracket kit #70-212-01 or projector mountable with optional bracket kit #70-217-01
Enclosure type	Metal
Enclosure dimensions	1.7" H x 2.2" W x 3.0" D (1U high, one-eighth rack wide) 4.3 cm H x 5.6 cm W x 7.6 cm D (Depth excludes connectors.)
Product weight	0.7 lbs (0.3 kg)
Shipping weight	3 lbs (2 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL UL rated for use in a plenum air space: meets UL2043 and UL60950 for fire and smoke.
Compliances	CE, FCC Class A, VCCI, AS/NZS, ICES
Warranty	3 years parts and labor

NOTE All nominal levels are at $\pm 10\%$.

NOTE Specifications are subject to change without notice.

(7.51-020106-D4-111612)