

Specifications — IPA T RLY4

Relay control

Relay control ports number/type	4 momentary
Relay control connectors	(1) 3.5 mm captive screw connectors, 5 pole, for control input and power (4) 3.5 mm captive screw connectors, 3 pole, NO and NC for configurable relay outputs
Relay coil operating current	0.015 A
Relay control contact rating	24 V, 1 A

General

Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	Tabletop
Enclosure type	Plastic
Enclosure dimensions	1.0" H x 2.4" W x 2.3" D (2.5 cm H x 6.1 cm W x 5.8 cm D)
Product weight	0.1 lbs (<0.1 kg)
Shipping weight	1 lb (1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI
Warranty	3 years parts and labor

NOTE All nominal levels are at $\pm 10\%$.

NOTE Specifications are subject to change without notice.

7.6-091409-D61" " " " #