

## Specifications

### IPCP Pro 360

#### Memory

SDRAM.....	512 MB
Flash.....	4.5 GB

#### Software

Configuration software .....	Global Configurator® Plus and Professional
Programming software.....	Global Scripter®
Control apps.....	Extron Control
Resource management software....	GlobalViewer® Enterprise
Utilities .....	Toolbelt, embedded web page

#### Hardware user interface

Hardware .....	TouchLink® Pro touchpanels, NBP button panels, or eBUS® button panels
----------------	---

#### Ethernet

Network interface controllers (NICs)	2: 1 LAN, 1 AV LAN
Network switch.....	1 AV LAN unmanaged 3 port switch
Connectors .....	LAN: 1 female RJ-45 connectorAV LAN: 3 female RJ-45 connectors
Data rate.....	10/100/1000Base-T, half/full duplex with autodetect
Protocols .....	DHCP, DNS, HTTP (redirect), HTTPS, ICMP, IEEE 802.1X, NTP, SFTP, SMTP, SNMP, SSH, TCP/IP, UDP/IP
Default settings	
LAN.....	Link speed and duplex level = autodetected IP address = 192.168.253.250 Subnet mask = 255.255.255.0 Gateway = 0.0.0.0 DHCP = off DNS = 127.0.0.1
AV LAN.....	Link speed and duplex level = autodetected DHCP server = disabled Subnet mask = 255.255.255.0 Gateway = 0.0.0.0
DHCP server disabled.....	IP address = 192.168.254.250 DNS = 127.0.0.1
DHCP server enabled .....	IP address = 192.168.254.1 DNS = 192.168.254.1 Dynamic leased IP address pool = 192.168.254.100 - 192.168.254.149 Maximum lease count = 50 Lease time = 24 hours

## Specifications • IPCP Pro 360 (Continued)

### Serial

Quantity/type .....	1 bidirectional RS-232, RS-422, RS-485 (port 1) 2 bidirectional RS-232 (ports 2 and 3)
Connectors .....	(1) 3.5 mm captive screw connector, 5 pole (2) 3.5 mm captive screw connectors, 3 pole
Baud rate and protocol .....	300 to 115200 baud (9600 baud = default); 8 (default) or 7 data bits; 1 (default) or 2 stop bits; no parity (default), even, or odd parity

**NOTE:** The 5-pole ports support both hardware and software flow control.  
The 3-pole ports support software flow control.  
The default for both types of ports is no flow control.

#### Pin configurations

##### Serial, 5-pole captive screw

RS-232 (default).....	Pin 1 = Tx, 2 = Rx, 3 = Gnd, 4 = RTS, 5 = CTS
RS-422.....	Pin 1 = Tx-, 2 = Rx-, 3 = Gnd, 4 = Tx+, 5 = Rx+
RS-485.....	Pins 1 and 2 (tied together) = data-, 3 = Gnd, 4 and 5 (tied together) = data+
Serial, 3-pole captive screw.....	Pin 1 = Tx, 2 = Rx, 3 = Gnd

### Digital I/O

Quantity/type .....	4 digital input/output (configurable)
Connectors .....	(1) 3.5 mm captive screw connector, 5 pole
Digital inputs	
Input voltage range.....	0 to 24 VDC, clamped at +30 VDC
Input impedance .....	>10k ohms
Programmable pullup .....	1k ohms to +5 VDC
Threshold low to high .....	2.8 VDC
Threshold high to low .....	2.0 VDC
Digital outputs.....	250 mA sink from 24 VDC max.
Pin configurations .....	1, 2, 3, 4 = digital I/Os 1, 2, 3, 4; 5 = Gnd

### IR/serial

Quantity/type .....	2 programmable: unidirectional RS-232 ( $\pm 5$ V), or TTL level (0 to 5 V) infrared (carrier and non-carrier) up to 300 kHz
Connector.....	(1) 3.5 mm captive screw connector, 5-pole
Baud rate and protocol (RS-232) ...	300 to 115200 baud (9600 baud = default); 8 (default) or 7 data bits; 1 (default) or 2 stop bits; no parity (default), even, or odd parity
Pin configurations .....	For each port, pin 1 = signal, 2 = Gnd
IR output carrier frequency.....	30 kHz to 300 kHz
IR learning carrier frequency.....	30 kHz to 300 kHz
IR learning capture distance.....	2" (5.1 cm) to 12" (30.5 cm) from the front panel

### Relay

Quantity/type .....	4 normally open relays
Relay control connectors .....	(1) 3.5 mm captive screw connector, 6 pole
Relay control contact rating.....	24 VDC, 1 A

### eBUS control

eBUS control ports .....	(1) 3.5 mm captive screw connector, 5 pole (uses 4 poles)
eBUS pin configuration .....	+V = +12 VDC; +S = + signal; -S = - signal; G = ground
Recommended cable type.....	Extron STP20-2/1000 or STP20-2P/1000 cable
Maximum system cable length.....	1000 feet (305 meters) sum total for the eBUS system, regardless of topology. Power injection may be required depending on system cabling topology and primary power supply wattage. See the <i>eBUS Technology Reference Guide</i> for details.
eBUS power output .....	6 watts

## Specifications • IPCP Pro 360 (Continued)

### Switched PoE+ power output

Quantity/type .....	2 switched PoE+ outputs
Connectors .....	2 female RJ-45 connectors (2 AV LAN ports)
Power .....	Maximum 30 watts per port
Power sense	
Range .....	0 watt to 30 watts
Resolution .....	0.3 watts

### General

Power supply .....	Internal
	Input: 100-240 VAC, 50-60 Hz
Power consumption .....	72.8 watts
	10.1 watts, 100-240 VAC, 50-60 Hz without eBUS or PoE+ output
Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
	Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling .....	Convection, no vents
Thermal dissipation .....	56.8 BTU/hr
	34.3 BTU/hr without eBUS or PoE+ output
Mounting	
Rack mount .....	Yes, with optional 1U rack shelf
Enclosure type .....	Metal
Enclosure dimensions .....	1.7" H x 8.7" W x 10.5" D (1U high, half rack wide)
	(43 mm H x 221 mm W x 267 mm D)
	(Depth excludes connectors.)
Product weight .....	3.0 lbs (1.2 kg)
Regulatory compliance .....	CE, C-Tick, c-UL, FCC Class A, ICES, KC, UL, VCCI
	Complies with the appropriate requirements of RoHS, WEEE
Product warranty .....	3 years parts and labor
Everlast power supply warranty .....	7 years parts and labor

**NOTE:** All nominal levels are at  $\pm 10\%$ .

**NOTE:** Specifications are subject to change without notice.

**NOTE:** Shipping weights and dimensions are available at [www.extron.com](http://www.extron.com).

5856-D7