

Specifications

USB HUB4 Series

USB

USB standards	USB 2.0, USB 1.1, USB 1.0 compatible
USB data rates	Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480 Mbps)

USB host

Number/signal type.....	1 USB
Connectors	1 female USB mini B <i>or</i> 1 female 3.5 mm captive screw connector, 5 pole (Only one port is active at a time.)

USB device ports

Number/signal type.....	(1) 4-port, USB hub
Connectors	4 female USB 2.0 type A
Maximum built-in USB hubs.....	1
Minimum built-in USB hubs.....	1
Optional built-in USB hubs.....	0
Available USB power.....	500 mA shared between 4 ports

General

Power	100 VAC to 240 VAC, 50-60 Hz, external; to 12 VDC, 1 A, regulated
Power input	12 VDC, 300 mA
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	
Rack mount.....	Yes, with optional mounting frame
Furniture mount	Yes with optional mounting frame or Extron devices with AAP or MAAP openings
Enclosure type	Metal
Enclosure dimensions	
USB HUB4 AAP	
Faceplate.....	1.4" H x 3.5" W x 0.1" D (35 mm H x 89 mm W x 3 mm D) (double space AAP plate)
Device	1.4" H x 1.4" W x 1.2" D (35 mm H x 35 mm W x 30 mm D) Allow at least 1.5" (38 mm) depth in the wall or furniture.
USB HUB4 MAAP	
Faceplate.....	1.4" H x 2.2" W x 0.1" D (36 mm H x 56 mm W x 3 mm D) (double space MAAP plate)
Device	1.4" H x 1.4" W x 1.2" D (35 mm H x 35 mm W x 30 mm D) Allow at least 1.4" (35 mm) depth in the wall or furniture.
Product weight	0.25 lbs (0.1 kg)
Shipping weight	1 lb (<1 kg)
Regulatory compliance.....	CE, C-tick, c-UL, FCC Class A, ICES, UL, VCCI Class A
Product warranty	3 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$.

Specifications • USB HUB4 Series (Continued)

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

5492-D5