

IN9210 Rack-Mountable DC Power Supply



The **IN9210** is a rack mountable DC power supply for the **IN2111Q** / **IN2111FT** / **IN2111F8** / **IN2114** / **IN2114F8** / **IN2114M** installation interfaces and other products which use an external 9VDC or 12VDC power transformer. The **IN9210** has 10 Phoenix brand 2-pin connectors for DC output and can power up to 10 products with a cumulative current of up to 3.0 amps.

Clean Up Your Equipment Rack - The **IN9210** promotes a clean equipment rack for installations using several products with external DC transformers since it can eliminate up to 10 "wall wart" power supplies.

2-Conductor Power Cable - The **IN8500** is a 2-conductor shielded power cable that connects the **IN9210** power output to the installation interface's power input. **IN8500** cable is available in bulk rolls. For installer convenience, the **IN8510** power cable is available. This 10' long power cable is designed for Inline products with a round DC power input connector and comes pre-terminated with an **IN9318** 2-pin Phoenix connector and an **IN9305** DC power plug.

Universal Power Supply - The **IN9210** is a high efficiency switch mode power supply that operates worldwide with voltages from 90-260V.

Rack Mountable - Two **IN9210** can be rack mounted side-by-side in a 2U space using an **IN9081** rack shelf. A single **IN9210** may be rack mounted using an **IN9081** rack shelf and an **IN9085** blank panel.



Tel 714. 921. 4100
Fax 714. 921. 4160

FEATURES

- Single Power Supply Powers Up to Ten Products with a Cumulative Current of 3 Amps
- 12VDC Regulated Power Supply - Compatible with Products Which Use a 9VDC or 12VDC Unregulated External Power Supply
- Phoenix Brand Captive Screw Terminals for Output
- Switch Mode Transformer for Worldwide Compatibility: 90-260VAC ; 47-63 Hz

SPECIFICATIONS

POWER:

Power Output Connectors: (10) 2-Pin Captive Screw Terminal
Output Voltage: 12 Volts DC - Regulated
Max. Output Current: 3 Amps
Power Supply: Internal Universal: 90 to 260 VAC; 47 to 63Hz

GENERAL:

Dimensions: 3.4" x 8.5" x 4.4" / 8.6cm x 21.6cm x 11.2cm
Shipping Weight: 4 lbs. / 2 kg
Product Weight: 2.2 lbs. / 1 kg
Included Accessories: (10) IN9318 2-Pin Male Captive Screw Connector
Regulatory Approvals: UL1950, CAN/CSA-22.2 No.950, Third Edition
CE: EN55022 (1987), EN50081-1 (1991), EN50082-1 (1992 and 1994), EN60950-92
MTBF: 150,000 Hours

MTBF calculated per MIL-HDBK-217D, parts count method, benign environment, ground, fixed